

<u>BTCPower's Newest Level 2 Dual-Port Pedestal Charging Station</u> <u>A Dual Level 2 Charger with Internal Cord Management System</u>



Features:

- ✓ Dual-Port charger
- ✓ Lanyard cord retracting systems
- √ 30 amp rated per side
- ✓ Dual Level 2 AC charger
- ✓ Credit card reader or contactless reader
- √ 7 inch color outdoor display
- J1772 coupler
- ✓ DSL, Wi-Fi, Zigbee or cellular wireless capable



TCPOWER

TECHNICAL SPECIFICATIONS

AC Power Input	208/240 VAC, Single Phase
Amperage	16A, 30A, 40A / per side
Required Service Panel	20A - 50A, double pole, non-GFCI type on dedicated
Breaker	circuit / per side
Output Charging Power	3.3kW - 9.6kW / per side
Charging Connector	SAE J1772, 25' cable
Ground Fault Detection	Build-in, 5mA trip
Surge Protection	6kV @ 3000A - IEC 61000-4-4
Operating Temperature	-30°C to +55°C
Operating Humidity	90% RH, non-condensing
Enclosure	NEMA 3R
User Interface	7" touch screen display or LEDs
Payment System	Credit Card and/or RFID
Power Measurement	Revenue grade energy meter
Network	Wired and Wireless

